

# Merker Washing machine topLine pro 8940, 9240



## topLine pro 8940

- Load capacity: 7 kg
- Large 4.3" colour display
- Drum vanes for 3D-Washing
- Drum capacity: 60 l
- Spin speed: 1600 rpm
- g factor 690
- Residual moisture 43%
- With drain valve or drain pump
- Language selection button
- profiClean programme button
- 94 profiClean and 24 freely programmable slots
- USB-interface for PC software
- Door hinge right or left



## topLine pro 9240

- Load capacity: 8 kg
- Large 4.3" colour display
- Drum vanes for 3D-Washing
- Drum capacity: 70 l
- Spin speed: 1600 rpm
- g factor 690
- Residual moisture 43%
- With drain valve or drain pump
- Language selection button
- profiClean programme button
- 94 profiClean and 24 freely programmable slots
- USB-interface for PC software
- Door hinge right or left
- Anthracite or chrome steel finish

# Washing machine topLine pro

Company or brand name	Merker	Merker
Type of appliance	Washing machine	Washing machine
Type or sales description	topLine pro 8940	topLine pro 9240
Product number		
Model with drain pump (P)	8940.1EPU	9240.1EPU
Model with drain valve (V)	8940.1EUV	9240.1EUV
<b>Application features</b>		
Load capacity	max. kg 7	8
Drum capacity	l 60	70
Spinning speed	max. rpm 1600	1600
g factor	g 690	690
Residual moisture <sup>1)</sup>	% 43	43
<b>Structural design</b>		
Footed appliance with work surface	•	•
Door hinge <sup>2)</sup>	r/l/w	r/l/w
<b>Dimensions</b>		
Height	cm 90	90
Width	cm 63	63
Depth including distance from wall	cm 72	72
Depth with door open (front loader)	cm 116	116
Height (adjustable)	cm 1	1
Weight when empty	kg 100	102
<b>Equipment</b>		
Detergent tank and drum	chrome-nickel steel	chrome-nickel steel
Loading opening	∅ cm 34 /180°	34 /180°
Automatic door opening	•	•
Connecting cable	m 1,6	1,6
Drain		
- Drain hose with benda, only model (P)	m 1,5	1,5
- Model with drain pump (P)	∅ mm 21	21
- Model with drain valve (V)	∅ mm 50	50
<b>Electric power and water supply</b>		
Electrical connection <sup>3)</sup>		
Voltage / connected loads / fuse	400 V 2 N~ / 50Hz / 4,6kW / 10A 230 V 1 N~ / 50Hz / 2,3kW / 10A	400 V 3 N~ / 50Hz / 4,6kW / 10A 400 V 2 N~ / 50Hz / 4,6kW / 10A 230 V 1 N~ / 50Hz / 2,5kW / 13A 230 V 1 N~ / 50Hz / 2,3kW / 10A
Water connection		
- Pressure hose G 3/4" with fine filter	m 1,5	1,5
- Can be connected to cold water / hot water	cold water / hot water 70 °C	cold water / hot water 70 °C
- Water pressure	bar 1-10	1-10
<b>Options</b>		
		- Execution in chrome steel
	- Door hinge left	- Door hinge left
	- Drain valve or drain pump	- Drain valve or drain pump
	- USB-interface for PC software	- USB-interface for PC software
	- RFD-Card-System	- RFD-Card-System
	- Connection for 8 liquid detergents with dosing pump	- Connection for 8 liquid detergents with dosing pump
	- Machine plinth	- Machine plinth
	- Machine plinth with lint trap drawer	- Machine plinth with lint trap drawer
<b>Safety and service</b>		
Conforms to the European Machinery Directive	2006/42/EC	2006/42/EC
Country of origin	Switzerland	Switzerland
Guarantee	1year	1year
Service by	Merker Maschinen AG	
Name and address of supplier	Merker Maschinen AG, CH-8633 Wolfhausen/ZH	

## Explanations:

- Available or yes      • Not available or no

1) Values determined in the 60°C cotton programme.

2) Door hinge: l = left, r = right, w = can be changed  
Example: l/w means that the machine is delivered with the door hinge to the left, but the direction of opening can be changed.

3) Information on switchover options can be found in the installation instructions, where required.